

6808

MATERIAL SAFETY  
DATA SHEET

Stretchcoat Inc  
11703 E. Washington Blvd  
Whittier Ca 90610  
(562) 696-1370

24-HOUR  
EMERGENCY  
TELEPHONE  
(800) 519-4119

FOAM & FABRIC ADHESIVE  
NON CHLORINATED WEB SRRAY,AERO

PRODUCT ID NO.: 1995

PAGE: 1

\*\*\*\*\*

EFFECTIVE DATE: 07/18/02  
PRODUCT ID NO.: 6808

DATE PREPARED: 09/12/02

=====  
This Material Safety Data Sheet contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community right to know emergency response reporting requirements under SARA TITLE III and many other laws. If you resell this product, this MSDS must be given to the buyer or the information incorporated in your MSDS.  
=====

This MSDS complies with 29 CFR 1910.1200  
(The Hazard Communication Standard)

=====  
SECTION I - PRODUCT IDENTIFICATION  
=====

PRODUCT DESCRIPTION: FOAM & FABRIC ADHESIVE  
NON CHLORINATED WEB SRRAY,AERO

D.O.T. PROPER SHIPPING NAME: ORM-D

CONSUMER COMMODITY

NFPA CODES: HEALTH - 1 FLAMMABILITY - 3 CORROSIVE - 0 REACTIVITY - 0

=====  
SECTION II - COMPONENTS  
=====

ALIPHATIC HYDROCARBON \* PEL: 500 PPM....  
CAS #: 110-54-3 TLV: 50 PPM

PETROLEUM HYDROCARBON RESIN PEL: NONE ESTABLISHED  
CAS #: ACCESSION NO.219873 TLV: NONE ESTABLISHED

STYRENE-ISOPRENE BLOCK COPOLYMER PEL: NOT HAZARDOUS UNDER OSHA  
CAS #: 025038-32-8 TLV: NOT HAZARDOUS UNDER OSHA

CYCLOHEXANE PEL: NONE ESTABLISHED  
CAS #: 110-82-7 TLV: NONE ESTABLISHED

METHYL ETHYL KETONE \* PEL: 100 PPM  
CAS #: 78-93-3 TLV: 100 PPM

XYLENE \* PEL: 100 ppm  
CAS #: 1330-20-7 TLV: 100 ppm

ACETONE \* PEL: TWA 1000 PPM  
CAS #: 67-64-1 TLV: TWA 750 PPM STEL 1000 PPM

## MATERIAL SAFETY

FOAM & FABRIC ADHESIVE  
NON CHLORINATED WEB SPRAY, AERO

PRODUCT ID NO.: 1995

PAGE: 2

\*\*\*\*\*  
 ===== SECTION II - COMPONENTS (CONTINUED) =====  
 HYDROCARBONS, --PROPANE PEL: 800 PPM  
 CAS #: 68-476-86-8 TLV: 800 PPM

"\*" If present, IARC, NTP and OSHA carcinogens and chemical subject to this reporting requirements of SARA TITLE III, SECTION 313 are identified in this section.

===== SECTION III - PHYSICAL DATA =====  
 BOILING POINT FOR PRODUCT: -44 TO 302 F.  
 VAPOR PRESSURE FOR PRODUCT: 50PSIG@75F  
 VAPOR DENSITY FOR PRODUCT: HEAVIER THAN AIR  
 SPECIFIC GRAVITY: 0.81  
 V.O.C. (GRAMS PER LITER): N/A: AEROSOL < 55%  
 WATER SOLUBILITY: SLIGHT  
 APPEARANCE: GRAYISH LIQUID  
 VOC-WEB SPRAY ADHES: CARB < 55 %

===== SECTION IV - FIRE AND EXPLOSION DATA =====  
 FLASH POINT (TCC): LEVEL 3 AEROSOL  
 EXPLOSIVE LIMIT (PRODUCT): LOWER - 1.0 UPPER - 6.0  
 04.20

## GENERAL HAZARD:

Combustible liquid, can form combustible mixtures at temperatures at or above the flashpoint. Static Discharge, material can accumulate static charge which can cause an incendiary electrical discharge. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT cut, weld, braze, solder, drill or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.

## FIRE FIGHTING:

Use water spray to cool fire exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. Use foam, dry chemical, or water spray to extinguish fire. Avoid spraying water directly into storage containers due to danger of boilover. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

===== SECTION V - HEALTH HAZARD DATA =====

05.20

GENERAL: This material is an aspiration hazard and defats the skin. Breathing vapors of high concentrations may cause CNS depression.

EYE CONTACT: Slightly irritating but does not injure eye tissue.

SKIN CONTACT: Low order of toxicity. Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an existing dermatitis condition.

INHALATION: High vapor/aerosol concentrations (greater than approximately 100 ppm) are irritating to the eyes and the respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

MATERIAL SAFETY  
DATA SHEETFOAM & FABRIC ADHESIVE  
NON CHLORINATED WEB SRRAY,AERO

PRODUCT ID NO.: 1995

PAGE: 3

\*\*\*\*\*

## ===== SECTION V - HEALTH HAZARD DATA (CONTINUED) =====

INGESTION: Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly minimal toxicity.

## FIRST AID

EYE CONTACT: Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

SKIN CONTACT: Flush with large amounts of water; use soap if available. Remove grossly contaminated clothing, including shoes, and launder before reuse.

INHALATION: Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention

INGESTION: If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

## PRECAUTIONS

SPECIAL PRECAUTIONS: Health studies have shown that many hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

PERSONAL PROTECTION: For open systems where contact is likely, wear safety glasses with side shields, long sleeves, and chemical resistant gloves. Where concentrations in air may exceed the limits, work practice or other means of exposure reduction are not adequate, NIOSH/MSHA approved respirators may be necessary to prevent overexposure by inhalation.

VENTILATION: The use of mechanical dilution ventilation is recommended whenever this product is used in a confined space, is heated above ambient temperatures, or is agitated.

(PROPOSITION 65):SEC05

State of California SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986.

WARNING: IN ACCORDANCE WITH PROP 65, THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS AND OTHER REPRODUCTIVE HARM.

## ===== SECTION VI - REACTIVITY DATA =====

06.20

STABILITY: stable

CONDITIONS TO AVOID: Not applicable

HAZARDOUS POLYMERIZATION: will not occur

MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY: Strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: None

## ===== SECTION VII - SPILL OR LEAK PROCEDURES =====

SEC07.45

STEPS TO BE TAKEN IN CASE CONTAINER IS PUNCTURED AND MATERIAL IS RELEASED:

Clean up area by mopping or with absorbant materials and place

Page 3

MATERIAL SAFETY  
DATA SHEETFOAM & FABRIC ADHESIVE  
NON CHLORINATED WEB SRRAY,AERO

PRODUCT ID NO.: 1995

PAGE: 4

\*\*\*\*\*

===== SECTION VII - SPILL OR LEAK PROCEDURES (CONTINUED) =====  
 in closed container for disposal. Consult Federal, State, and local  
 disposal authorities.

WASTE DISPOSAL METHOD: Consult local authorities for proper waste disposal  
 procedures. Empty de-pressurized containers can not be reused. Cans  
 which are pressurized or contain liquid must be disposed of in a per-  
 mitted waste management facility. Consult Federal, State, and local  
 disposal authorities for approved procedures.

===== SECTION VIII - PROTECTIVE EQUIPMENT TO BE USED =====

SEC08.20

VENTILATION REQUIREMENT: Use adequate level exhaust ventilation. Note: Where  
 carbon monoxide may be generated, special ventila-  
 tion may be required.

Local exhaust recommended when appropriate to  
 control employee exposure.

RESPIRATORY PROTECTION: Based on contamination level and working limits of  
 the respirator, use a respirator approved by NIOSH/MSHA.

EYES: Face shield and goggles or chemical goggles should be worn.

GLOVES: Impervious gloves should be worn. Gloves contaminated with the  
 product should be discarded. Polyfluorinated polyethylene has  
 been suggested.

OTHER CLOTHING EQUIPMENT: Standard work clothing.  
 Standard work shoes; discard if shoes cannot be decontaminated.  
 Store contaminated clothing in well ventilated cabinets or closed  
 containers. Wash contaminated clothing and dry before reuse.

RESPIRATORY PROTECTION: In situations where vapor concentrations exceed the  
 recommended exposure limits, a NIOSH approved organic vapor cartridge  
 or air-supplying respirator should be worn.

===== SECTION IX - SPECIAL PRECAUTIONS OR OTHER COMMENTS =====

SEC09.45

HANDLING STORAGE AND DECONTAMINATION PROCEDURES: When utilizing pressurized  
 containers follow standard safety practices for handling aerosols.

GENERAL COMMENTS: Do not store at temperatures above 120 degree F. Odor is  
 not an adequate warning of potentially hazardous concentrations in  
 air. Releases of these gases may cause a flammable atmosphere with  
 explosion potential.

PRECAUTIONARY STATEMENTS: Please read and follow the directions on the  
 product label. They are your best guide to using this product in  
 the most effective way, and give the necessary safety precautions  
 to protect your health.

MATERIAL SAFETY  
DATA SHEET

FOAM & FABRIC ADHESIVE  
NON CHLORINATED WEB SRRAY,AERO

PRODUCT ID NO.: 1995

PAGE: 5

\*\*\*\*\*

==== SECTION IX - SPECIAL PRECAUTIONS OR OTHER COMMENTS(CONTINUED) ==

===== ADDITIONAL COMMENTS =====

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.